

## Outdoor units

AZQS-B(8)V1 (A) / AZQS-BY1 (A)



### Ideal solution for busy environments and small shops

- › Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall
- › With a gas cooled PCB reliable cooling is guaranteed as it is not influenced by ambient temperature
- › Outdoor units are fitted with either a swing or scroll compressor, renowned for low noise and high energy efficiency
- › Exclusively offered for pair applications (capacity from 71 up to 140)

# AZQS-B(8)V1 (A) / AZQS-BY1 (A)




## Pair application

Capacity class	FCQG-F				ADEQ-C				ABQ-C				AHQ-C			
	71	100	125	140	71	100	125	140	71	100	125	140	71	100	125	140
AZQS-B(8)V1	P	P	P	P	combines with ARXS	P	P						P	P	P	P
AZQS-BY1		P	P	P						P	P	P		P	P	P

Outdoor unit				AZQS	71B1V1(A)	100B8V1(A)	125B8V1(A)	140B8V1(A)	100BY1(A)	125BY1(A)	140BY1(A)
Dimensions	Unit	HeightxWidthxDepth	mm	770x900x320	990x940x320	1,430x940x320	990x940x320	1,430x940x320	990x940x320	1,430x940x320	1,430x940x320
Sound power level	Cooling	Nom.	dBA	64	70	71		70		71	70
	Heating	Nom.	dBA	50	57	58		54	57	58	54
	Night quiet mode	Level 1	dBA	43				49			
Operation range	Cooling	Ambient	Min.-Max.	°CDB	-5~46						
	Heating	Ambient	Min.-Max.	°CWB	-15~15.5						
Refrigerant	Type/Charge/GWP	kg/TCO <sub>2</sub> eq		R-410A/2.75/5.7/2,087.5	R-410A/2.9/6.1/2,087.5	R-410A/4.0/8.4/2,087.5	R-410A/4.0/8.4/2,087.5	R-410A/2.9/6.1/2,087.5	R-410A/4.0/8.4/2,087.5	R-410A/4.0/8.4/2,087.5	
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240			3N~/50/380-415				

Contains fluorinated greenhouse gases | EER/COP according to Eurovent 2012, for use outside EU only

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN17-135

01/17



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.