



Outdoor units for pair application

AZQS-B(8)V1/AZQS-BY1

- › Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall
- › With gas cooled PCB reliable cooling is guaranteed as it is not influenced by ambient temperature (single phase)
- › Exclusively offered for pair application (capacity from 71 up to 140 class)

AZQS-B(8)V1/BY1




Capacity class		ABQ-D				ACQ-D				AHQ-C			
		71	100	125	140	71	100	125	140	71	100	125	140
AZQS71B2V1		1				1				1			
AZQS100B8V1	AZQS100BY1		1				1				1		
AZQS125B8V1	AZQS125BY1			1				1				1	
AZQS140B8V1	AZQS140BY1				1				1				1

Outdoor unit			AZQS	71B1	100B8V1	125B8V1	140B8V1	100BY1	125BY1	140BY1
Dimensions	Unit	HeightxWidthxDepth	mm	770x900x320	990x940x320		1,430x940x320	990x940x320		1,430x940x320
Sound power level	Cooling		dBA	64	70	71	70		71	70
Sound pressure level	Cooling	Nom.	dBA	48	53	54	53		54	53
	Heating	Nom.	dBA	50	57	58	54	57	58	54
	Night quiet mode	Level 1	dBA	43						49
Operation range	Cooling	Ambient	Min.--Max.			-5~46				
	Heating	Ambient	Min.--Max.			-15~-15.5				
Refrigerant	Type/GWP			R-410A/2,087.5						
	Charge	kg/TCO ₂ eq		2.75/5.7	2.9/6.1		4.0/8.4	2.9/6.1		4.0/8.4
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240			3N~/50/380-415			

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-135 05/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.