



Wall mounted unit

FTXC-A



Inverter



Fan only



Powerful mode



Autocooling-heating
changeover



Comfortable sleeping
mode

Wall mounted unit, offering good value for money and ensuring a steady supply of clean air

- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › Seasonal efficiency values up to A+ in cooling and heating
- › Whisper quiet in operation down to 21 dBA

- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency

FTXC-A + RXC-A




Indoor unit		FTXC	25A	35A	50A	60A
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	288x859x209		310x1,124x237	
Sound power level	Cooling		53	54	55	61
Sound pressure level	Cooling	Super high/High/Low/Silent	41/40/29/21	42/41/30/22	44/40/35/32	46/43/37/33

Efficiency data		FTXC + RXC	25A + 25A	35A + 35A	50A + 50A	60A + 60A	
Cooling capacity	Nom.	kW	2.56	3.37	5.48	6.23	
Heating capacity	Nom.	kW	2.84	3.58	5.62	6.40	
Power input	Cooling	Nom.	693	1,060	1,668	1,931	
	Heating	Nom.	780	1,000	1,520	1,630	
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A++				
		Pdesign	kW	2.56	3.37	5.48	6.24
		SEER		6.14	6.11	6.79	6.21
	Heating (Average climate)	Energy efficiency class	A+				
		Pdesign	kW	2.41	2.19	3.57	4.16
		SCOP/A		4.00		4.30	4.21
Nominal efficiency	EER		3.08	2.63	3.54	3.44	
	COP		3.64	3.58	3.70	3.93	
	Annual energy consumption	kWh	-				

Outdoor unit		RXC	25A	35A	50A	60A
Dimensions	Unit	HeightxWidthxDepth	550x658x289		628x855x328	753x855x328
Sound power level	Cooling		58	60	64	65
Sound pressure level	Cooling	High	45	46	51	
Operation range	Cooling	Ambient	Min.-Max.	10~46		-10~46
	Heating	Ambient	Min.-Max.	-15~18		
Refrigerant	Type/Charge/GWP	kg/TCO ₂ eq	R-32/0.60/0.41/675	R-32/0.80/0.54/675	R-32/1.10/0.74/675	R-32/1.20/0.81/675
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com using: www.certiflash.com

ECPEN17-045

05/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.