



Daikin Altherma low temperature split

EHSB-A



Guaranteed
operation down
to -25°C

Floor standing air to water heat pump for
bivalent heating and hot water with thermal
solar support

- › Bivalent system: combinable with a secondary heat source
- › Integrated solar unit, maximising renewable energy and offering top comfort in heating and hot water
- › Solar support of domestic hot water with unpressurised (drainback) solar system
- › Lightweight plastic tank with exceptional hygienic benefits
- › App control possible for managing heating and hot water operation
- › Outdoor unit extracts heat from the outdoor air, even at -25°C

EHSB-A + ERLQ-CV3/CW1




Efficiency data		EHSB + ERLQ		04P30A + 004CV3	08P30A + 006CV3	08P50A + 006CV3	08P30A + 008CV3	08P50A + 008CV3	16P50A + 011CV3	16P50A + 014CV3	16P50A + 016CV3	16P50A + 011CW1	16P50A + 014CW1	16P50A + 016CW1	
Heating capacity	Nom.	kW		4.53/3.98/4.26/3.47	6.06/5.78/5.14/4.60		7.78/7.27/5.53/5.51		11.80/10.40/5.95/7.74	14.80/13.73/8.28/9.57	15.34/14.86/8.04/10.05	11.80/10.40/5.95/7.74	14.80/13.73/8.28/9.57	15.34/14.86/8.04/10.05	
Power input	Heating	Nom.		kW		0.87/1.04/1.49/1.05	1.30/1.58/1.88/1.26	1.69/2.04/1.98/1.56	2.57/3.13/2.48/2.35	3.42/4.07/3.17/2.93	2.57/3.13/2.48/2.35	3.42/4.07/3.17/2.93	2.57/3.13/2.48/2.35	3.42/4.07/3.17/2.93	
COP						5.23/3.84/2.85/4.07	4.65/3.66/2.73/3.64	4.60/3.57/2.78/3.54	4.38/3.32/2.45/3.29	4.27/3.34/2.58/3.22	4.10/3.22/2.44/3.15	4.38/3.32/2.45/3.29	4.27/3.34/2.58/3.22	4.10/3.22/2.44/3.15	
Space heating	Average climate	General	η_{sp} (Seasonal space heating efficiency)	%		130	125	127	125	126	125	126	125	125	
	water outlet 55°C	Seasonal space heating eff. class						A++							
Domestic hot water heating	Average climate	General	η_{wh} (water heating efficiency)	%											
	Declared load profile				L		XL	L	99	XL					
Water heating energy efficiency class								A							

Indoor Unit		EHSB		04P30A	08P30A	08P50A	08P30A	08P50A	16P50A			
Casing	Colour	Traffic white (RAL9016) / Dark grey (RAL7011)										
	Material	Impact resistant polypropylene										
Dimensions	Unit	HeightxWidthxDepth		mm		1,945x615x595	1,945x790x790	1,945x615x595	1,945x790x790			
Weight	Unit	kg		92	119	92	119	121				
Tank	Water volume	l		300	500	300	500					
	Maximum water temperature	°C						85				
Operation range	Heating	Ambient	Min.~Max.	°C		-25~25		-25~35				
		Water side	Min.~Max.	°C				15~55				
	Domestic hot water	Ambient	Min.~Max.	°CDB				-25~35				
Refrigerant	Type							R-410A				
	Charge	kg		1.5	1.6		3.4					
	Control	TCO ₂ eq						-				
Sound power level	Nom.	dBA						2,087.5				
		dBA						40				
Sound pressure level	Nom.	dBA						28				

Outdoor Unit		ERLQ		004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1	
Dimensions	Unit	HeightxWidthxDepth		mm		735x832x307		1,345x900x320					
Weight	Unit	kg		54	56		113		114				
Compressor	Quantity							1					
	Type					Hermetically sealed swing compressor		Hermetically sealed scroll compressor					
Operation range	Cooling	Min.~Max.		°CDB		10.0~43.0		10.0~46.0					
	Domestic hot water	Min.~Max.		°CDB		-25~35		-20~35					
Refrigerant	Type							R-410A					
	GWP							2,087.5					
	Charge	TCO ₂ eq		3.1	3.3				7.1				
Sound power level	Heating	Nom.	dBA		61		62		64	66	64	66	66
			dBA		63		64		66	69	64	66	69
			dBA		48		49		50		51	52	51
Sound pressure level	Heating	Nom.	dBA		48		49		50		51		52
			Cooling	Nom.	dBA		48	49		50	52	54	50
Power supply	Name/Phase/Frequency/Voltage	Hz/V					V3/1~/50/230		W1/3N~/50/400				
Current	Recommended fuses	A		16		20		40		20			

Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) | Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) | EW 30°C, LW 35°C; ambient conditions: -7°CDB/-8°CWB | EW 30°C; LW 35°C; ambient conditions: 2°CDB/1°CWB | Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



CEPEN16-753 10/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.